





GE  
Lighting

## 20867 - Q50MR16C/CG40

GE ConstantColor® Precise™ MR16

- UV protection



### CAUTIONS & WARNINGS

#### Caution

- Lamp may shatter and cause injury if broken
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Burn
  - Allow lamp/fixture to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Do not use lamp if outer glass is scratched or broken.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in fixture rated for this product.

### GENERAL CHARACTERISTICS

Lamp Type	Halogen - MR
Bulb	MR16
Base	2-Pin (GU5.3)
Filament	C-6
Rated Life	6000.0 hrs
Lamp Enclosure Type (LET)	Covered glass

### PHOTOMETRIC CHARACTERISTICS

Center Beam Candlepower (CBCP)	1500.0
Color Temperature	3050.0 K
Beam Spread	40.0 °

### ELECTRICAL CHARACTERISTICS

Wattage	50.0
Voltage	12.0
Burn Position	Universal burning position

### DIMENSIONS

Maximum Overall Length (MOL)	1.8750 in(47.6 mm)
Bulb Diameter (DIA)	2.000 in(50.8 mm)

### PRODUCT INFORMATION

Product Code	20867
Description	Q50MR16C/CG40
ANSI Code	EXN
Standard Package	BUNDLE
Standard Package GTIN	00043168208673
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168994194