

Hi-Spot ES63/ESD63

HS ES63 240V 75W 25° GU10 SV1

0022274



Product features

-

UV STOP



COOL
BEAM

PRODUCT OVERVIEW

Average life (Nominal) (h)	2500
Lamp finish	GU10/ES63+GZ10/ESD63
Colour temperature (K)	2800
Product EAN number	5410288222745
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Retail, Residential & Consumer
Product code	0022274
Cap/Base	GU10
Type	Hi-Spot ES63/ESD63
Wattage (W)	75
Light colour	828 Homelight
Luminous flux (lm)	700
Product name	HS ES63 240V 75W 25° GU10 SV1
Watt (Rated) (W)	75
Technology	Halogen
E-number Sweden	8355954
E-number Finland	4749398
E-number Norway	3700112
ETIM Class	EC000266

DATA TABLE

General data

Lamp finish	GU10/ES63+GZ10/ESD63
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Retail, Residential & Consumer
Product code	0022274
Cap/Base	GU10

Hi-Spot ES63/ESD63

HS ES63 240V 75W 25° GU10 SV1

0022274

Type	Hi-Spot ES63/ESD63
Product name	HS ES63 240V 75W 25° GU10 SV1
Watt (Rated) (W)	75
Technology	Halogen
E-number Sweden	8355954
E-number Finland	4749398
E-number Norway	3700112
ETIM Class	EC000266

Optical data

Colour temperature (K)	2800
Light colour	828 Homelight
Lumen maintenance at end of nominal life (%)	80
Luminous flux (lm)	700
Luminous flux (Rated) (lm)	700
Beam angle (Rated) (°)	25
Adjustable chromaticity	N

Electrical data

Control gear required	No
Current (A)	0.313
Drive current (mA)	0
Energy efficiency level	D
kWh per 1000 hours burning time	75
Lamp power factor	1
Wattage (W)	75
Mains voltage (V)	240V~
Starting time (max) (s)	0
Warm-up time to 60% of full light (max) (s)	Instant Full Light
Lamp Energy Label (class)	D
No. Of switching cycles before premature failures	>10000

Lifetime data

Average life (Nominal) (h)	2500
Average life (Rated) (h)	2500

Physical data

Weight (kg)	0.076
Max. Lamp Diameter (mm) - D	64

Hi-Spot ES63/ESD63

HS ES63 240V 75W 25° GU10 SV1

0022274


Packaging

Product EAN number	5410288222745
Packaging single height (cm)	6.0
Packaging single length (cm)	6.8
Single packaging type	Carton
Packaging single width (cm)	6.0
Units per outer package	15
Packaging outer height (cm)	8.5
Packaging outer length (cm)	32.0
Packaging outer width (cm)	21.0

Safety data

Breakage cleaning instructions	Not applicable
Suitable for household illumination	No
Intended purpose	General lighting
Recommendation for disposal at end of life	Not applicable
Special purpose lamp	No
Suitable for accent lighting	Yes

TECHNICAL DRAWINGS



Hi-Spot ES63/ESD63

HS ES63 240V 75W 25° GU10 SV1

0022274

