



GE
Lighting



Halogen Linear High Watt

TU*K5 1500W 230V R7S 254MM BX GE
1/10MIH

29184

Product information

Housing in a clear quartz bulb, these halogen floodlighting lamps have a ceramic one-pin cap on each end and can be operated on 230V or 240V mains. Linear halogen lamps provide a powerful light source for compact fittings used for floodlighting, architectural lighting and security. GE's linear halogen lamps are double ended, using the universal R7s cap format, and are available in the two industry standards of 118mm or 78mm, plus longer, higher wattage versions.

Product data

| | |
|-----------------------------|-----------------------|
| Cap/Base | R7s |
| Bulb Shape | Tubular |
| Bulb Diameter [mm] | 10 |
| Maximum Overall Length [mm] | 255.5 |
| Net weight per piece [g] | 20 |
| Gross weight per piece [g] | 41 |
| Brand | General Electric (GE) |

Performance data

| | |
|---|----------|
| Colour Rendering Index (CRI) [Ra] | 100 |
| Nominal correlated colour temperature (CCT) [K] | 3000 |
| Nominal lumens [lm] | 32000 |
| Rated efficacy [lm/W] | 21.33333 |
| Energy efficiency class (EEC) | D |
| Rated Life [h] | 2000 |
| Weighted energy consumption [kWh/1000h] | 1539.4 |

Electrical data

| | |
|--------------------------|------|
| Nominal power [W] | 1500 |
| Nominal lamp voltage [V] | 230 |
| Coil type | C-8 |
| Dimming Capability | Yes |

Logistic data

| | |
|--------------------------|---------------------|
| DUN Code | 39004102291849 |
| EAN Code | 9004102291848 |
| Pack Quantity | 10 |
| Layer quantity | 180 EUR, 240 UK |
| Layer quantity EUR | 180 |
| Layer quantity UK | 240 |
| Pallet quantity EUR (PC) | 2520 |
| Pallet quantity UK (PC) | 4080 |
| Outer case size | 381 x 124 x 60 (mm) |
| Product status | Available |

Application areas



Home



Hospitality

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Halogen Lamps Spectrum Catalogue \(PDF\)](#)

[Halogen DEQ and IR™ DEQ Lamps Data sheet \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)