











Halogen Linear

OT K12 C100W 230V R7S 78MM GE BX1/10MIC

63519

Product information

C class Double Ended Linear

- Increased efficiency C energy class
- More than 30% energy saving
- Retrofit to standard Double Ended Linear
- Full range 100-330W to replace 150-500W standard range

Application areas











Product data

Product Code	63519
Bulb Shape	Tubular
Bulb Diameter [mm]	10
Maximum Overall Length [mm]	78
Net weight per piece [g]	6
Gross weight per piece [g]	9
Brand	General Electric (GE)
Cap/Base	R7s

Performance data

Rated Lumens [lm]	1800
Weighted energy consumption [kWh/1000h]	106
Energy efficiency class (EEC)	D
Lamp Lumen Maintenance factor (2000 hours)	80%
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]]	2800
Nominal lumens [lm]	1800
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	100.0
Starting time (sec)	0.0 s
Warm up time up to 60% of full light output	instant
Number of switching cycles	8000
Dimming Capability	Yes
Nominal power [W]	100
Nominal lamp voltage [V]	230





Logistic data

DUN Code	10043168635193
EAN Code	0043168762106
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	4800 EUR, 6000 UK
Layer quantity EUR	4800
Layer quantity UK	6000
Pallet quantity EUR (PC)	24000
Pallet quantity UK (PC)	30000
Outer case size	191 x 188 x 212 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Halogen Lamps Spectrum Catalogue (PDF)

Halogen DEQ and IR™ DEQ Lamps Data sheet (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)