

**18**  
kWh/1000h

**A**  
energy class

**69**  
lumens/watt

## Biax™ L LongLast™ 4-pin, External Starter Req.

F18W BX/T5/840/4P TU

93105961

### Product information

Biax™ L covers a range of single ended compact fluorescent lamps with high lumen output and are available in a wide range: 18, 24, 34, 36, 40, 55 and 80 watt versions. The single ended design is less than half the length of standard fluorescent lamps. This makes Biax™ L the ideal choice for modular luminaires. The range is available in colours of 2700, 3000, 3500, and 4000K allowing use in most environments. All Biax™ L lamps have a CRI of 82. The family of Biax™ L lamps offers a rated life\* of 10,000 hours for 18W to 36W and 20,000 hours for 40, 55 and 80W. The 40, 55 and 80W versions are for use on high-frequency electronic gear only.

- at 3 hours per start

Long single biaxial tubes

### Application areas



Office



Industrial





Biax™ L LongLast™ 4-pin, External Starter  
Req.  
F18W BX/T5/840/4P TU  
93105961

Product data

Product Code	93105961
Bulb Shape	Biax Plug-in
Bulb maximum overall diameter [mm]	43.8
Maximum Overall Length [mm]	231.3
Net weight per piece [g]	85
Gross weight per piece [g]	106
Operating position	U - Universal
Mercury Content [mg]	3
UV radiance	exempt
Brand	Tungsram
Cap/Base	2G11

Performance data

Colour Code	840
Rated Lumens [lm]	1250
Weighted energy consumption [kWh/1000h]	17.6
Energy efficiency class (EEC)	A
Rated Life [h]	10000
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	1250
Colour Rendering Index (CRI) [Ra]	82



Biax™ L LongLast™ 4-pin, External Starter

Req.

F18W BX/T5/840/4P TU

93105961



Electrical data

Rated power [W]	16.0
Operating Temperature (MIN) [°C]	-15
Starting ambient temperature range	-15
Dimming Capability	Yes
Nominal power [W]	18
Nominal lamp voltage [V]	58


Logistic data

Shipment	Standard
DUN Code	15994100011054
EAN Code	5994100011057
Pack Quantity	25
Layer quantity	600 EUR, 700 UK
Layer quantity EUR	600
Layer quantity UK	700
Pallet quantity EUR (PC)	2400
Pallet quantity UK (PC)	2800
Outer case size	266 x 141 x 238 (mm)
Product status	Available

Technical drawing



## Survival data



## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[CFL Non-Integrated Spectrum Catalogue \(PDF\)](#)

[LongLast™ Biax™ L Data sheet \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)