


TUNGSRAM™

Innovation is our heritage
EST. 1896



23
kWh/1000h

B
energy class

67
lumens/watt

Biax™ T 2-pin with Amalgam, Internal Starter

F18W TBX/T4/827/A/2P TU

93105928

Product information

Ultra compact energy saving CFL lamps with triple-tube design give an ideal light source for small fixtures and downlighters. Biax™ T lamps allow more compact fixture designs with the same lumen output as Biax™ D lamps. They can also be used to deliver higher lumen output from existing designs. The Biax™ T & T/E lamps are electrically interchangeable with Biax™ D and D/E lamps. They are available in 13, 18, 26, 32 and 42W. Light output ranges between 900 and 3200 lumens. Biax™ T/E lamps with a 4-pin electrical connection and without an internal starter are designed for high-frequency electronic ballasts. The use of separate electronic ballasts makes them suitable for almost every kind of energy supply: high and low voltages, accumulators, batteries, solar cells and systems that can be dimmed.





Biax™ T 2-pin with Amalgam, Internal Starter

F18W TBX/T4/827/A/2P TU
93105928

Application areas



Office



Industrial



Biax™ T 2-pin with Amalgam, Internal Starter

F18W TBX/T4/827/A/2P TU
93105928

Product data

Product Code	93105928
Bulb Shape	Hex plug-in
Bulb maximum overall diameter [mm]	49.3
Maximum Overall Length [mm]	127.4
Net weight per piece [g]	85
Gross weight per piece [g]	125
Operating position	U - Universal
Mercury Content [mg]	1.3
UV radiance	exempt
Brand	Tungsram
Cap/Base	GX24d-2

Performance data

Colour Code	827
Rated Lumens [lm]	1200
Weighted energy consumption [kWh/1000h]	22.1
Energy efficiency class (EEC)	B
Rated Life [h]	10000
Nominal correlated colour temperature (CCT) [K]	2700
Nominal lumens [lm]	1200
Colour Rendering Index (CRI) [Ra]	82



Biax™ T 2-pin with Amalgam, Internal Starter

F18W TBX/T4/827/A/2P TU

93105928


Electrical data

Rated power [W]	18.0
Operating Temperature (MIN) [°C]	-15
Starting ambient temperature range	-15
Dimming Capability	No
Nominal power [W]	18
Nominal lamp voltage [V]	100


Logistic data

Shipment	Standard
DUN Code	15994100010729
EAN Code	5994100010722
Pack Quantity	10
Layer quantity	320 EUR, 360 UK
Layer quantity EUR	320
Layer quantity UK	360
Pallet quantity EUR (PC)	1920
Pallet quantity UK (PC)	2160
Outer case size	263 x 110 x 154 (mm)
Product status	Available

Technical drawing



Survival data



Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[CFL Non-Integrated Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)