

Mini-Lynx Fast-Start V2

Mini-Lynx Fast-Start V2 15W E27 865 SLV

0035015



Product features

-

PRODUCT OVERVIEW

Lamp finish	Frosted
Lamp shape	CFLi Stick
Colour temperature (K)	6500
CRI (Ra)	80
Dimmable	No
EAN code	5410288350158
Energy class	A
Equivalent watt (W)	65
Cap/Base	E27
Type	Mini-Lynx Fast-Start V2
Watt (Nominal) (W)	15
Light colour	865 Daylight
Ordering number	0035015
Efficacy (Rated) (lm/w)	53.3333333333333
Average life (h) - L70/B50	12000
Luminous flux (Rated) (lm)	800
Technology	Compact Fluorescent
Voltage (V)	220-240

DATA TABLE

General data

Average life (h) at Ta 25° C	12000
Control gear required	No
Lamp finish	Frosted
Lamp shape	CFLi Stick
Dimmable	No
Dry applications use only	Yes
EAN code	5410288350158
Energy class	A

Mini-Lynx Fast-Start V2

Mini-Lynx Fast-Start V2 15W E27 865 SLV

0035015

Energy saving lamp	Yes
General application	Hospitality; Residential & Consumer;
Intended purpose	General lighting
Cap/Base	E27
Lamp mercury content (mg)	2
Type	Mini-Lynx Fast-Start V2
No. of switching cycles before premature failure (min)	30000
Optimal operating condition (°C)	25° C, cap-up, Stated lumen output may vary if operated in non-standard position
Ordering number	0035015
Product name	Mini-Lynx Fast-Start V2 15W E27 865 SLV
Average life (h) - L70/B50	12000
Special purpose lamp	No
Starting time (max) (s)	<1.0
Technology	Compact Fluorescent
Warm-up time to 60% of full light (max) (s)	< 40

Optical data

Colour temperature (K)	6500
CRI (Ra)	80
Light colour	865 Daylight
Lumen maintenance at end of nominal life (%)	0.7
Luminous flux (Nominal) (lm)	800
Luminous flux (Rated) (lm)	800

Electrical data

Current (A)	0.12
Equivalent watt (W)	65
kWh per 1000 hours burning time	15
Lamp power factor	0.55
Watt (Nominal) (W)	15
Efficacy (Rated) (lm/w)	53.33333333333333
Watt (Rated) (W)	15
Voltage (V)	220-240

Physical data

Max. Lamp Diameter (mm) - D	49
Lamp Length (mm) - C/L	125

Mini-Lynx Fast-Start V2

Mini-Lynx Fast-Start V2 15W E27 865 SLV

0035015

TECHNICAL DRAWINGS

