












Life in Light

MEGAMAN®

ULTRA COMPACT CANDLE

Model: CL811iCS/SE**Voltage (V):** 220-240**Wattage (W):** 11.0

Lamp Base	Lamp Life (hrs)	Diameter (mm)	Length (mm)	Lumen Output (lm)	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 60% of the Full Light Output (sec)	Switching Cycles (times)	Lumen Maintenance at the End of Lamp Life (%)
					Ra	PF			 x ? times	(%)
Warm White (2700K)										
E14	15,000	43	125	531	80	≥0.50	<2.0	<120	600,000	≥75
E27	15,000	43	121	531	80	≥0.50	<2.0	<120	600,000	≥75

**Operating Temperature (°C) :** -10 to +40**Mercury Content (mg):** 2.0**Clean-up Procedures in Case of Lamp Breakage:** <http://www.megaman.cc/clean-up>**Disposing of Lamp at its End of Life:** <http://www.megaman.cc/disposal>











Life in Light

MEGAMAN®

ULTRA COMPACT CANDLE

Model: CL811iCS/SE**Voltage (V):** 220-240**Wattage (W):** 11.0

Lamp Base	Lamp Life (hrs)	Diameter (mm)	Length (mm)	Lumen Output (lm)	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 60% of the Full Light Output (sec)	Switching Cycles (times)	Lumen Maintenance at the End of Lamp Life (%)
					Ra	PF				(%)
Day Light (6500K)										
E14	15,000	43	125	500	80	≥0.50	<2.0	<120	600,000	≥75
E27	15,000	43	121	500	80	≥0.50	<2.0	<120	600,000	≥75

**Operating Temperature (°C) :** -10 to +40**Mercury Content (mg):** 2.0**Clean-up Procedures in Case of Lamp Breakage:** <http://www.megaman.cc/clean-up>**Disposing of Lamp at its End of Life:** <http://www.megaman.cc/disposal>