

Lamps for Special Applications Designer Color Lamps

Description: HIT 70W/G12/UVS/BDX

Performance Data


Dominant Wavelength	462
% Saturation	77
Rated Life (Hrs @ 10Hr./Start)	3000
Chromaticity (CIE - X Y)	180,99
Typical Warm Up Time (Minutes)	1-2
Typical Hot Restart Time (Minutes)	2-4
Burning Position	Universal

Physical Data

Base Designation	G12
Bulb Designation	T23
Bulb Diameter (mm)	23
Max. Overall Length (mm)	110
Light Centre Length (mm)	56
Effective Arc Length (mm)	9
Max. Base Temperature (°C)	280
Max. Bulb Temperature (°C)	650
Luminaire Type	Enclosed
Socket Pulse Rating (KV)	6
Mercury Content (mg)	11

Lamp Electrical Data

IEC Standard	61167
Nominal Lamp Wattage (W)	70
Lamp Operating Voltage (V)	85
Lamp Operating Current (A)	0.9
Min. Open Circuit Voltage (RMS)	198
Min. Starting Pulse (Peak V)	1800-4500
Min. Pulse Width (Microseconds)	1 @2700V
Min. Pulse Rate Per ½ cycle	1
Pulse Position (Electrical Degrees)	60-90, 240-270



Revision: 01-03-2012

See page 2 for product notes

Lamps for Special Applications Designer Color Lamps

Notes:

This Product Specification contains data about typical performance at nominal power. Actual values may depend on ballast and applications. Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives.