





GE Precise™ MR16 Dimmable LED7XD/MR16G/827/12V/25 BX 1/8 **93048796**

Product information

GE's newest LED technology surpasses current market expectations for MR16 performance. Improved lumen output and an outstanding 45,000 hours life rating for a high quality halogen MR16 replacement. Available in three colour temperatures and two beam angles. The new Constant Colour™ 35W has a smooth heat sink and provide high colour consistency within 4 steps on the MacAdam ellipse. The new 50W has up to 15% higher lumen output.

Application areas



Hospitality





Product data

| Product Code | 93048796 |
|------------------------------------|--|
| Bulb Shape | Mirrored reflector |
| Bulb Finish | White |
| Bulb maximum overall diameter [mm] | 50 |
| Nominal Length [mm] | 45.5 |
| Net weight per piece [g] | 60 |
| Dimmability | Yes |
| RoHS compliant | Yes |
| Brand | GE BX |
| Cap/Base | GU5.3 |
| Standard Warranty Period | 3 years with maximum 12000 burning hours |

Performance data

| Nominal/ Rated Beam Angle [°] | 25 |
|--|---------|
| Colour consistency | 4 steps |
| Nominal center beam candlepower (CBCP) [cd] | 2350 |
| Useful lumens (at 90° cone) [lm] | 470 |
| Rated efficacy [lm/W] | 71 |
| Energy efficiency class (EEC) | A+ |
| Rated life L70/B50 [h] | 45000 |
| Nominal correlated colour temperature (CCT) [K]] | 2700 |
| Nominal lumens [lm] | 500 |
| Colour Rendering Index (CRI) [Ra] | 80 |





Electrical data

| Nominal lamp power factor | 0.8 |
|----------------------------------|-------|
| Operating Temperature (MIN) [°C] | -5°C |
| Operating Temperature (MAX) [°C] | +40°C |
| Starting time (sec) | <0.5s |
| Number of switching cycles | 90000 |
| Dimming Capability | Yes |
| Nominal lamp voltage range [V] | 12 |
| Nominal power [W] | 7 |

Logistic data

| DUN Code | 10064894549301 |
|-----------------|----------------|
| EAN Code | 0064894549304 |
| Pack Quantity | 8 |
| Inner pack type | Box |
| Outer pack type | Carton |
| Product status | Available |

Downloads & Links Go to the catalog site (HTTP) Product datasheet (PDF) Dimming compatibility (HTTP) Transformer compatibility (HTTP) Lighting design tools & calculators (HTTP) Datasheets (HTTP) Images (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)