







GE Energy Smart™ PAR38 Outdoor

LED18/P38/827/90-240V/25/E27 BX 1/6

13387

Product information

GE's new LED PAR range combines a high intensity spotlight beam with substantial energy savings. The PAR38 design delivers a dazzling 7,000 candelas and 120W equivalent Lumen output from only 18W of power, saving nearly 90% in energy consumption. Additionally, the 40,000 hours L70 life time offers significant reduction to maintenance costs by sharply reducing replacement frequency. GE PAR38 is applicable for wet locations as well (IP65 design).

Application areas



) Retail



Hospitality









Product data

Cap/Base	E27
Bulb Shape	PAR
Bulb Finish	Coated
Bulb Diameter [mm]	123
Maximum Overall Length [mm]	132
Net weight per piece [g]	340
Gross weight per piece [g]	653
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	84
Nominal correlated colour temperature (CCT) [K]	2700
Nominal beam angle [°]	25
Rated beam angle [°]	25
Nominal center beam candlepower (CBCP) [cd]	7600
Nominal lumens [lm]	1400
Rated Lumens [Im]	1200
Useful lumens (at 90° cone) [lm]	1200
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	40000
Weighted energy consumption [kWh/1000h]	18





Electrical data

Nominal power [W]	18
Rated power [W]	18.0
Nominal lamp power factor	0.9
Nominal lamp voltage [V]	230
Lamp Current [A]	0.22
Operating Temperature (MAX) [°C]	40
Run-up time (sec)	<1s
Starting time (sec)	<0.5s
Number of switching cycles	40000
Dimming Capability	No


Logistic data


DUN Code	10043168133873
EAN Code	0043168133876
Pack Quantity	6
Inner pack type	BOX
Layer quantity	36 EUR, 54 UK
Layer quantity EUR	36
Layer quantity UK	54
Pallet quantity EUR (PC)	180
Pallet quantity UK (PC)	270
Outer case size	423 x 282 x 210 (mm)
Product status	Available







Photometric Data








Technical drawing



Spectral distribution







GE Energy SmartTM PAR38 Outdoor LED18/P38/827/90-240V/25/E27 BX 1/6

13387

Downloads & Links

Go to the catalog site (HTTP)

Photometry (IES)

LED Lighting Solutions - Catalogue (EN) (PDF)

LED PAR20/30/38 Lamps - Data sheet (PDF)

Dimming compatibility (HTTP)

Lighting design tools & calculators (HTTP)

Datasheets (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)