
TUNGSRAM

Innovation is our heritage EST. 1896







Tungsram Bright Stik™ LED 6/STIK/830/220-240V/E27/F 3/15 TU 93110192

Product information

LED Bright Stik™ illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years*. That's a long time you can spend not worrying about light bulbs.

Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years*
- 3 colour options 3000K, 4000K & 6500K
- Always ready instant brightness
- No mercury worry-free use and disposal



- Warranty: 2 years with maximum 8 000 burning hours according to Tungsram Standard Warranty conditions
- Based on 2.7 hours of per day use.



Product data

Product Code	93110192
Bulb Shape	T38
Bulb Finish	White
Bulb maximum overall diameter [mm]	38
Nominal Length [mm]	115.5
Net weight per piece [g]	41
Dimmability	No
RoHS compliant	Yes
Brand	Tungsram
Cap/Base	E27

Performance data

Nominal/ Rated Beam Angle [°]	240
Rated Lumens [lm]	470
Weighted energy consumption [kWh/1000h]	6.0
Rated efficacy [lm/W]	78.3
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	15000
Nominal correlated colour temperature (CCT) [K]]	3000
Nominal lumens [lm]	470
Colour Rendering Index (CRI) [Ra]	80




Electrical data

Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Starting time (sec)	<0,5 s
Power Factor	>0.5
Warm up time up to 60% of full light output	Instant on
Number of switching cycles	50k
Nominal lamp voltage range [V]	220-240V
Nominal power [W]	6.0

Logistic data

DUN Code	15994100027390
EAN Code	5994100027393
Pack Quantity	15
Product status	Available

Photometric Data





Downloads & Links

Go to the catalog site (HTTP)
Photometry (IES)
Product datasheet (PDF)
Images (HTTP)

