

9  
kWh/1000h

A+  
energy class

94  
lumens/watt

## Tungsram Bright Stik™

LED 9/STIK/865/220-240V/E27/F 3/15  
TU

93110195

### Product information

LED Bright Stik™ illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years\*. That's a long time you can spend not worrying about light bulbs.

#### Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
  - To fit in more fixtures compared to CFL
  - Optimised for omni-directional light distribution
  - Space-saving benefits on-shelf
  - 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years\*
- 3 colour options - 3000K, 4000K & 6500K
- Always ready - instant brightness
- No mercury - worry-free use and disposal

- Warranty: 2 years with maximum 8 000 burning hours according to Tungsrām Standard Warranty conditions
  - Based on 2.7 hours of per day use.
-

## Product data

Product Code	93110195
Bulb Shape	T38
Bulb Finish	White
Bulb maximum overall diameter [mm]	38
Nominal Length [mm]	115.5
Net weight per piece [g]	42
Dimmability	No
RoHS compliant	Yes
Brand	Tungsram
Cap/Base	E27

## Performance data

Nominal/ Rated Beam Angle [°]	240
Rated Lumens [lm]	850
Weighted energy consumption [kWh/1000h]	9.0
Rated efficacy [lm/W]	94.4
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	15000
Nominal correlated colour temperature (CCT) [K]	6500
Nominal lumens [lm]	850
Colour Rendering Index (CRI) [Ra]	80


## Electrical data

Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Starting time (sec)	<0,5 s
Power Factor	>0.5
Warm up time up to 60% of full light output	Instant on
Number of switching cycles	50k
Nominal lamp voltage range [V]	220-240V
Nominal power [W]	9.0

## Logistic data

DUN Code	15994100027420
EAN Code	5994100027423
Pack Quantity	15
Product status	Available

## Photometric Data



## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Photometry \(IES\)](#)

[Product datasheet \(PDF\)](#)

[Images \(HTTP\)](#)



Tungsrám is a registered trademark of  
Tungsrám Operations Kft.

[tungsrám.com](http://tungsrám.com)

We in Tungsrám Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsrám cannot accept any liability arising from the reliance on such data to the extent permitted by law.