## **TUNGSRAM**

Innovation is our heritage EST. 1896





# LED Stik LED14/STIK/865/220-240V/E27/F 2/10 93120148

## **Product information**

LED Stik illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years\*. That's a long time you can spend not worrying about light bulbs.

Features & benefits

- · LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W
   bulb
- Rated life of 15 years\*
- 3 colour options 3000K, 4000K & 6500K
- Always ready instant brightness
- No mercury worry-free use and disposal
- Warranty: 2 years with maximum 8 000 burning hours



LED Stik LED14/STIK/865/220-240V/E27/F 2/10 93120148

according to Tungsram Standard Warranty conditions

• Based on 2.7 hours of per day use.

# Application areas









### Product data

Product Code	93120148
Product description	LED14/STIK/865/220-240V/E27/F 2/10
Nominal Length [mm]	137
Net weight per piece [g]	75
Dimmability	No
Brand	Tungsram
Cap/Base	E27

#### Performance data

Color consistency (SDCM)	6
Rated efficacy [lm/W]	114.29
Energy efficiency class (EEC)	Е
Rated life L70/B50 [h]	15 000
Input Frequency [Hz]	50/60
Nominal correlated colour temperature (CCT) [K]]	6500
Nominal lumens [lm]	1600
Colour Rendering Index (CRI) [Ra]	80

#### Electrical data

Nominal lamp power factor	0.7
Operating Temperature (MIN) [°C]	-10
Operating Temperature (MAX) [°C]	40
Starting time (sec)	0.5
Number of switching cycles	30 000
Nominal lamp voltage range [V]	220-240
Nominal power [W]	14



### Logistic data

Shipment	Standard
DUN Code	15994100085963
EAN Code	5994100085966
Pack Quantity	2/10
Product status	Available

#### Downloads & Links

Go to the catalog site (HTTP)
Link to EPREL (HTTP)
Datasheet (PDF)
Images (HTTP)
Declaration of Conformity (PDF)