# **JIUNGSRAM**<sup>™</sup>

Innovation is our heritage EST.1896





### Dimmable Bright Stik™ LED DimSTIK 14(100)840 E27 TU 93104214

## **Product information**

TUNGSRAM keeps innovating and introduces the Dimmable Bright Stik to complete the most successful range\* in the LED lamps to replace CFL and eCFL.

 Bright Stik<sup>™</sup> Led Lamp range won the IDEA Bronze design award in 2017 and the IF Design award in 2018

#### Application areas







🗑 Other



#### Product data

Product Code	93104214
Bulb Shape	T45
Bulb Finish	White
Bulb maximum overall diameter [mm]	45
Nominal Length [mm]	138
Net weight per piece [g]	69
Dimmability	Yes
RoHS compliant	Yes
Brand	Tungsram
Cap/Base	E27

#### Performance data

Nominal/ Rated Beam Angle [°]	240
Rated Lumens [lm]	1521
Weighted energy consumption [kWh/1000h]	14
Rated efficacy [lm/W]	108.64
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	15000
Nominal correlated colour temperature (CCT) [K]]	4000
Nominal lumens [lm]	1521
Colour Rendering Index (CRI) [Ra]	80

#### **Electrical data**

Nominal lamp power factor	>0.7
Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Starting time (sec)	<0.5 s
Warm up time up to 60% of full light output	Instant on
Number of switching cycles	50k
Nominal lamp voltage range [V]	220-240V 50/60Hz
Nominal power [W]	14

#### Logistic data

Shipment	Standard
DUN Code	15994100019999
EAN Code	5994100019992
Pack Quantity	15
Product status	Available

#### 120 135° 165 135° 180° 165 120 100 100 120° 80 120° 60 80 40 105° 105 60 90' 90° 75° 75° 40 60° 60° 45 45° 15 0° 30 180 135 135° 180° η = 96% 180-cd/klm \_\_\_\_\_C0 - C180 cd/klm \_\_\_\_\_C0 - C180 $\eta = 96\%$ C90 - C270 C90 - C270

#### Photometric Data

#### Downloads & Links

Go to the catalog site (HTTP) Photometry (IES) Product datasheet (PDF) Datasheet (PDF) Images (HTTP)



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.