

	 22 78 124 CE IP 20				
Reference	12403430				
Dimensions (LxWxH)	124x79x22				
Input	220-240V 50/60Hz				
Ambient temperature	-25°C to +45°C				
Power factor (max)	0.95				
Dimming	-				
Max drivers on MCB 16A type B	15				
Output	350mA / 25W 1-74V DC	500mA / 35W 1-72V DC	700mA / 50W 1-71V DC	900mA / 50W 1-55V DC	1050mA / 50W 1-48V DC
DIP-switch setting	ON OFF 1 2 3 4 5 6	ON OFF 1 2 3 4 5 6	ON OFF 1 2 3 4 5 6	ON OFF 1 2 3 4 5 6	ON OFF 1 2 3 4 5 6
Chapeau 206 LED GE	2	2			
Duell recessed 1x LED GE	3	3			
Duell recessed 2x LED GE	1	1			
Hipy 110 IP67 LED GE	3	3	3		
Hipy 70 IP67 LED GE	7				
Julien IP54 LED GE	5				
K72 IP54 LED GE	4	3			
K77 adjustable LED GE	4	3			
Kurk IP40 LED GE	3	3	3		
Kurk surface IP40 LED GE	3	3	3		
Lotis 82 (concrete) LED GE	3	3			
Lotis 86 IP55 LED GE	3	3			
Lotis 97 (concrete) adjustable LED GE	3	3			
Lotis square (IP55) LED GE	3	3			
Marcel 1x LED GE	2	2	2		
Marcel 2x LED GE	1	1	1		
Marcel 3x LED GE	1/2 *	1/2 *	1/2 *		
Marty LED GE	26				
Mini multiple 1x LED GE	3	3			
Mini multiple 2x LED GE	1	1			
Mini multiple 3x LED GE	1	1			
Mini multiple 4x LED GE					
M-LED 50 GE	4	3			
M-LED 70 GE	4	3			
M-LED 111 GE	2	2	2	1	
Médard ceiling recessed LED GE	2	2			
Nomad 111 2x LED GE	1	1	1		
Nomad 111 4x LED GE	1/2 *	1/2 *	1/2 *		
Nomad 70 2x LED GE	1	1			
Nomad 70 4x LED GE	1/2 *	1/2 *			
Rektor recessed LED GE	2	2			
Scotty 270 adjustable LED GE	1				
Scotty 270 LED GE	1	1			
Slide IP54 LED GE	4	3			
Smart cake / kup / lotis / asy lotis 48 (IP54) LED GE	26	25			
Smart cake / kup / lotis 82 (IP54) LED GE	3	3			
Smart cake / kup / lotis 115 adjustable LED GE	3	3			
Smart cake / kup / lotis 115 (diffuse) (IP54) LED GE	2	2	2	1	
Smart cake / kup / lotis 160 (diffuse) (IP54) LED GE		2	2	1	1
Stove LED GE	2	2			
(Asy) Wink 115 LED GE	2	2	2	1	

 driver does not fit through cutout hole of fixture

* requires 2 drivers

** requires 3 drivers