

Intro - Low Voltage downlight - IP65

GU5.3 50W

0053450



Range Features

- White or chrome finish
- Toughened frosted glass front lens
- Suitable for zone 1 or 2 as required by I.E.E. wiring regulations (UK only) (where water jets are likely to be used)



PRODUCT OVERVIEW

Beam angle(°)	38°
Colour	White
EAN code	5410288534503
Housing	Aluminium
IP rating	65
Lamps	1 x Coolfit 50W GU5.3
Mount	Ceiling recessed
Ordering number	0053450
Voltage (V)	12
Compatible with bulbs of energy class:	CD

DATA TABLE

Optical data

Beam angle(°)	38°
Distribution type	Direct adjustable
Optical controller finish	Toughened frosted
Optical controller material	Glass front lens

Physical data

Colour	White
Cutout diameter (mm)	73
Cutout shape	Round
Diameter (mm)	82
Diffuser finish	Frosted
Diffuser material	Glass
IP rating	65
Lamp included	No

Intro - Low Voltage downlight - IP65

GU5.3 50W

0053450

Recessed depth (mm)	95
Vertical tilt (°)	25°/30°
Weight (kg)	0.23
Outer package dimensions (L x W x H) (cm)	36.00 x 34.50 x 25.00
Single package dimensions (L x W x H) (cm)	11.80 x 9.00 x 6.60



General data

EAN code	5410288534503
Environment	Interior
General application	Residential & Consumer, Hospitalit
Housing	Aluminium
Mount	Ceiling recessed
Ordering number	0053450
Range features	White or chrome finish Toughened frosted glass front lens Suitable for zone 1 or 2 as required by I.E.E. wiring regulations (UK only) (where water jets are likely to be used)
Product name	GU5.3 50W
Specific application	Bedrooms Corridors Halls Kitchen / Cooking Restaurant Stairwell
Sales pack quantity	1
Compatible with bulbs of energy class:	CD

Electrical data

Electrical protection	Class III
Lamps	1 x Coolfit 50W GU5.3
Number of heads	1
Transformer availability	By others
Transformer mounting	Remote
Voltage (V)	12

TECHNICAL DRAWINGS



Intro - Low Voltage downlight - IP65

GU5.3 50W

0053450

