


# ENCASTRÉ DÉCORATIF 230V

## ELODY 10W




Corps et diffuseur polycarbonate blanc/Dissipateur aluminium. Orientable. Optique en retrait pour un bon confort visuel. Alimentation intégrée.

|     |  |  36°    |              |              |          |
|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------------|--------------|----------|
|     | 230V                                                                               | IP20                                                                                       | IK02         | 650°C        | 30 000 h |
| P (w)                                                                                | Lumens                                                                             | Teinte                                                                                     | Code         | € HT         |          |
|  10 | 950                                                                                |  3000 K | <b>50403</b> | <b>25,00</b> |          |
|  10 | 1000                                                                               |  4000 K | <b>50404</b> | <b>25,00</b> |          |

| 50403 | 3000 K                | 10 W  | 36° |
|-------|-----------------------|-------|-----|
| h (m) | E <sub>max</sub> (lx) | d (m) |     |
| 1     | <b>1728</b>           | 0,65  |     |
| 2     | <b>432</b>            | 1,3   |     |
| 3     | <b>192</b>            | 1,9   |     |

| 50404 | 4000 K                | 10 W  | 36° |
|-------|-----------------------|-------|-----|
| h (m) | E <sub>max</sub> (lx) | d (m) |     |
| 1     | <b>1873</b>           | 0,65  |     |
| 2     | <b>468</b>            | 1,3   |     |
| 3     | <b>208</b>            | 1,9   |     |

## ELODY 7W



Corps et diffuseur polycarbonate blanc/Dissipateur aluminium. Orientable. Optique en retrait pour un bon confort visuel. Alimentation intégrée.

|    |  |  36°    |              |              |          |
|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|--------------|--------------|----------|
|    | 230V                                                                                 | IP20                                                                                         | IK02         | 650°C        | 30 000 h |
| P (w)                                                                                 | Lumens                                                                               | Teinte                                                                                       | Code         | € HT         |          |
|  7 | 590                                                                                  |  3000 K | <b>50401</b> | <b>17,50</b> |          |
|  7 | 650                                                                                  |  4000 K | <b>50402</b> | <b>17,50</b> |          |

| 50401 | 3000 K                | 7 W   | 36° |
|-------|-----------------------|-------|-----|
| h (m) | E <sub>max</sub> (lx) | d (m) |     |
| 1     | <b>972</b>            | 0,65  |     |
| 2     | <b>243</b>            | 1,3   |     |
| 2,5   | <b>156</b>            | 1,6   |     |

| 50402 | 4000 K                | 7 W   | 36° |
|-------|-----------------------|-------|-----|
| h (m) | E <sub>max</sub> (lx) | d (m) |     |
| 1     | <b>1057</b>           | 0,65  |     |
| 2     | <b>264</b>            | 1,3   |     |
| 2,5   | <b>169</b>            | 1,6   |     |