



INTERNO - INCASSI CON CASSAFORMA
INDOOR - RECESSED WITH HOUSING



CRI > 90 3000K (M)
Alto indice di resa cromatica
High colour rendering index



2 STEP MACADAM 3000K
Elevata precisione cromatica
High chromatic precision



DGA COOLER MAX
Sistema di dissipazione brevettato
Patented heat dissipation system



Modulo LED sostituibile
Replaceable LED module



210

Gemma 50 i



IP52 con cassaforma
with housing



Class III



Incasso a parete, soffitto, pavimento
Wall, ceiling, floor recessed



Carrabile 2000 kg
Drive over up to 2000 kg



Lente 60° solo calpestabile
60° lens steppable only



Possibilità di scelta tra 6 differenti ottiche
Available in 6 different optics



Cavo 60 cm con connettore rapido
60 cm cable with quick connector




Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA



80 gr



ECO Energy Saving



Gemma 50 i
page 346

Alimentatori consigliati
Suggested drivers

350mA
CC20-F-350-N
page 551

500mA
CC20-F-500-N
page 552

350mA RGB
CC36-X-350-N
page 558

Accessori
Accessories



Cassaforma
Housing
A00103.30
page 551

Ø 42 mm

	1W 350mA	2W 500mA	3W 350mA
Lumen 3000K	100lm	150lm	300lm
10° Lens	730165. __	730166. __	
30° Lens	760165. __	760166. __	
60° Lens	750165. __	750166. __	750167. __
Vetro trasparente Transparent glass	720165. __	720166. __	720167. __
Vetro satinato Frosted glass	710165. __	710166. __	710167. __
Lente ellittica Elliptical lens	770165. __	770166. __	

www.dga.it/photometrics

LED COLOUR
FINISHING

	3W RGB 350mA
30° Lens	760616. _ 7
Vetro satinato Frosted glass	710616. _ 7

www.dga.it/photometrics

FINISHING

FINISHING

1 Cromo lucido - Shiny chrome
3 Grigio - Gray
6 AISI 316L
Acciaio inox.
Stainless Steel

LED COLOUR

Y 2700K
6 3000K
W 3000K **CRI > 90**
9 4000K
1 5000K