

DOWNLIGHT

WASH

7 W LED IP65




W	T°	LM	RÉFÉRENCES	DESCRIPTIONS LUMINAIRE
7W	3000K	604lm	LT-DW-7IPWW	Downlight MONO LED WASH 7W IP65 fixe 3000K + driver non dimmable
7W	4000K	704lm	LT-DW-7IP	Downlight MONO LED WASH 7W IP65 fixe 4000K + driver non dimmable

DRIVERS EN OPTION

W	RÉFÉRENCES	DESCRIPTIONS
7W	LCA-17-250-700	Driver TRIDONIC DALI/PUSH DIM 17W 250-700 mA Class I
7W	LCBI-8-350	Driver TRIDONIC gradation à la phase

DIM PHASE	NON DIMMABLE	DALI/ PUSH DIM	1/10 V	FINITION NOIRE	FINITION BLANCHE	DIMENSIONS
✓	✓	✓	✗	✗	RAL 9003	Ø Installation 75 mm

7 W		
H (m)	D (m)	Em (lx)
1	0,51	1335
3	1,54	148
4	2,57	53



DONNÉES TECHNIQUES

CE	RoHS NORME	TENSION ENTRÉE DRIVER 220-240v	COURANT SORTIE DRIVER 350 mA	350G	350G	350G
IK 07	IP 65	PF 09	Ø 75 mm	45°	UGR <19	IRC 82
SDCM <4	EN 62471 RG0	ENCASTRE	DURÉE DE VIE 40000 H	L80B20	850°	2000000
Driver LIFUD	LED BRIDGELUX	BORNIER À REPIQUAGE	BLANC MAT	GARANTIE 3 ans	FONTE D'ALUMINIUM	A+

OPTIONS

DALI	PUSH DIM	CONNECTEUR WIELAND 3P	CONNECTEUR WIELAND 5P
------	-------------	--------------------------	--------------------------