
ITUNGSRAM

Innovation is our heritage EST. 1896







Spotlight G1 5W

LED Spotlight G1 TU WRF IP65 5W 840 S

93100530

Product information

The Tungsram Recessed Spotlight G1 5W range has functional and minimalistic design with fix and adjustable versions. These LED Spotlights are ideal for small areas to make your ceilings seem higher, or when you are looking for directional lighting. Never was the installations easier and quicker with these products. The Recessed Spotlight G1 5W range offers all the benefits of LED lighting to our customers – fresh light quality, reduced energy consumption and less maintenance.



Product data

Mounting type	Recessed
Brand	TUNGSRAM
IP Rating	65
Certifications	CE
Body colour	White
Weight [kg]	0.110
DIALux description	TUNGSRAM - Spotlight G1 5W - 420lm - 5W - 4000K - 80CRI - 93100530[SKU] - Recessed
IEC protection classes	Class II
Dimensions	ø85x54mm
Energy efficiency class (EEC)	A+

Performance data

Operating Voltage	220-240V
Ambient Temperature [°C]	-10°C to +40°C
Rated efficacy [lm/W]	84
Total system power	5
Nominal lumens [lm]	420
Rated lumens [lm]	420
Rated power [W]	5
Rated life [h]	20000
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	80+

Optical data

Nominal beam angle [°]	36°
------------------------	-----

Electrical data


Nominal lamp power factor	0.5
---------------------------	-----


Controllability	Not dimma	ble e	electronic (Static)
-----------------	-----------	-------	---------------------


Logistic data

Product status	Available
Shipment	Standard

Photometric Data







Downloads & Links

Go to the catalog site (HTTP) Datasheet (PDF) Installation guide (PDF) Images (HTTP) DoC Document (PDF)