

RIVER MAXI

IP68 IK08 CE F III SUB A A+ A++

TIPOLOGIA / *TYPOLGY*


Incasso | *Recessed*

POSIZIONE INSTALLATIVA | *INSTALLATION POSITION*

A terra, a parete, a immersione | *Floor, wall, by immersion mounting*

AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION*

Esterno | *Outdoor*



RIVER MAXI

STANDARD VERSION: **4-6W**

RGBW-TW VERSION: **8W**



kg 0,93

RIVER MAXI

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	Standard version: 4-6W RGBW-TW version: 8W
ALIMENTAZIONE POWER SUPPLY	C.C. - 24Vdc (RGBW-TW versions C.C. only)
ALIMENTATORE POWER SUPPLY UNIT	2W - 500mA Non incluso Not included 4W - 350mA Non incluso Not included 6W - 500mA Non incluso Not included 2-6W - 24Vdc Non incluso Not included
DIMMERAZIONE DIMMING	Dimmerabile Push, DMX, DALI, 1-10V, taglio di fase, esclusa versione RGBW-TW <i>Push, DMX, DALI, 1-10V, phase cut dimmable, except RGBW-TW version</i>
COLLEGAMENTO CONNECTION	C.C. - Serie Series 24Vdc. - Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2700K, 3000K, 4000K, 5000K, Red, Green, Blue, RGBW, TW
INDICE RESA CROMATICA CRI CRI	>90 (2700K, 3000K, 4000K, 5000K)
OTTICHE OPTICS	8°, 16°, 30°, 40°, 64°, 16° x 41°, Diffused, ASYM, B. Light (RGBW-TW versions 30°, 40°, 64° lens only)
FLUSSO TOTALE NOMINALE TOTAL DELIVERED LUMENS	400-560lm (2700K) 440-600lm (3000K) 480-640lm (4000K)
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	kg 0,93
FINITURE FINISHES	Acciaio Steel
INSTALLAZIONE INSTALLATION	A incasso con cassaforma (non inclusa) <i>Recessed with housing box (not included)</i>
MATERIALE MATERIAL	Corpo in acciaio inox AISI 316L, ghiera in acciaio inox AISI 316L, vetro temperato trasparente e lente in PMMA <i>AISI 316L stainless steel body, AISI 316L stainless steel trim, transparent tempered glass and PMMA lens</i>

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP68
GRADO DI RESISTENZA IMPACT RESISTANCE	IK08
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	Sì Yes
CARRABILE DRIVE OVER	No
CAVI DI ALIMENTAZIONE POWER CABLES	Fornito con 8 m di cavo Provided with 8 m cable
SICUREZZA STANDARD STANDARD SAFETY	I
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1


RIVER MAXI

ACCESSORI | ACCESSORIES



STANDARD

a scelta | to be chosen

CODICE / CODE	CAW53
TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,10
MATERIALE MATERIAL	PVC



CODICE / CODE	CAI53
TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,06
MATERIALE MATERIAL	ABS



IP68

CODICE / CODE	CA853
TIPOLOGIA / TYPOLOGY	Cassaforma Housing box   kg 0,10
MATERIALE MATERIAL	PVC

