

Sylfast T8 - Non Compensated SYLFAST T8 158 NC

0046084



Range Features

- Range of T8 battens and accessories
- Available with Magnetic or Electronic ballast
- 1-10V dimmable versions available
- 3 hr emergency options available
- Made of roll-formed steel
- Punch out holes on both ends
- 3-pole terminal block











PRODUCT OVERVIEW

Certifications	CE
Colour	White
Dimmable	N/A
Dimming range	N/A
EAN code	5410288460840
Housing	Sheet steel
IK rating	IK02
IP rating	IP20
LOR (%)	N/A
Mount	Surface Mounted
Ordering number	0046084
Technology	Т8
Voltage (V)	220-240
Compatibile with bulbs of energy class:	A++

DATA TABLE

Ger	ıerai	l data	

Gerierar data	
Certifications	CE
Control gear type	Magnetic
Dimmable	N/A
EAN code	5410288460840
Environment	Internal
Fixture rating	Open
General application	Logistics and Industry
Housing	Sheet steel
Mount	Surface Mounted
Ordering number	0046084



Sylfast T8 - Non Compensated SYLFAST T8 158 NC

0046084

Range features	Range of T8 battens and accessories Available with Magnetic or Electronic ballast 1-10V dimmable versions available 3 hr emergency options available Made of roll-formed steel Punch out holes on both ends 3-pole terminal block
Product name	SYLFAST T8 158 NC
Technology	Т8
Compatibile with bulbs of energy class:	A++
Product features	Non compensated magnetic ballast SSE-T8 1x58W
Physical data	
Colour	White
Emergency duration (h)	N/A
Emergency mode	N/A
Height (mm)	74
IK rating	IK02
IP rating	IP20
Lamp included	No
Length (mm)	1527
Weight (kg)	1.88
Width (mm)	51
Optical data	
Dimming range	N/A
LOR (%)	N/A
Electrical data	
Electrical protection	CLASS I
Glow wire test	850
Voltage (V)	220-240

TECHNICAL DRAWINGS





Sylfast T8 - Non Compensated SYLFAST T8 158 NC

0046084



