

## Sylproof LED

SYLPROOF LED 44W 1265MM T 4000K

0047883



## Range Features

- IP65 LED Waterproof Batten with high output and high efficacy. 44W LED is equivalent to 2x36W Fluorescent.



## PRODUCT OVERVIEW

Certifications	CE
Colour temperature (K)	4000
Colour	Grey
CRI (Ra)	80
Dimmable	Non-dim / not dimmable (switched only)
EAN code	5410288478838
Luminous flux (lm)	4357
Housing	Polycarbonate
IK rating	8
IP rating	65
Light colour	Neutral White
LOR (%)	100
Mount	Surface
Ordering number	0047883
Efficacy (Rated) (lm/w)	100
Average life (Rated) (h)	50000
Technology	LED
Voltage (V)	220-240
Included lamp	Integrated LED
Compatible with bulbs of energy class:	A++

## DATA TABLE

## General data

Average life (Nominal) (h)	50000
Certifications	CE
Control gear type	Electronic
Dimmable	Non-dim / not dimmable (switched only)
EAN code	5410288478838
Environment	Internal

# Sylproof LED

SYLPROOF LED 44W 1265MM T 4000K

0047883

General application	Logistics and Industry
Housing	Polycarbonate
Mount	Surface
Ordering number	0047883
Range features	IP65 LED Waterproof Batten with high output and high efficacy. 44W LED is equivalent to 2x36W Fluorescent.
Product name	SYLPROOF LED 44W 1265MM T 4000K
Average life (Rated) (h)	50000
Technology	LED
Compatible with bulbs of energy class:	A++
Tender text	Weather and Vandal resistant 44W LED luminaire 4357lm output with heat resistant robust polycarbonate body (IK08). UV stabilised polycarbonate diffuser with linear prisms designed to optimise light output and to reduce glare. Stainless steel diffuser clips and fixing brackets for surface mounting. Retained diffuser for easy maintenance. As Sylvania Sylproof Superia LED

## Optical data

Colour temperature (K)	4000
CRI (Ra)	80
Distribution type	Direct
Luminous flux (lm)	4357
Light colour	Neutral White
LOR (%)	100

## Physical data

Colour	Grey
Diffuser finish	Clear
Diffuser material	Polycarbonate
Height (mm)	91
IK rating	8
IP rating	65
Lamp included	Yes
Length (mm)	1265
Reflector finish	Polycarbonate Diffuser
Weight (kg)	2.38
Width (mm)	123
Included lamp	Intergrated LED

## Electrical data

Drive current (mA)	600
Electrical protection	CLASS I
Glow wire test	850
Efficacy (Rated) (lm/w)	100

## Sylproof LED

SYLPROOF LED 44W 1265MM T 4000K

0047883

<b>Ta rating</b>	-30°C to +30°C
<b>Total power consumption (W)</b>	43.6
<b>Voltage (V)</b>	220-240

### PHOTOMETRY

