
# **TUNGSRAM**

Innovation is our heritage EST. 1896







T5 Batten ECO
LBTE 8 WW 2ft ECO
93044478

## **Product information**

The LED T5 Batten designed to be a direct replacement for conventional battens, with energy savings. It offers multiple installation methods to ease your worries and bring the customer a brand new experience of soft lighting. Switch free luminaires. The best choice for smooth linear lighting. We offer this range of 8 luminaires in 4 wattages.



# Product data

Mounting type	Surface mount
Brand	GE Lighting
IP Rating	20
Certifications	CE/EAC
Body colour	White
Weight [kg]	0.11
DIALux description	TUNGSRAM - T5 Batten ECO - 750lm - 8W - 3000K - 80CRI - 93044478[SKU] - Surface mount
IEC protection classes	Class II
Impact resistance (IK)	IK02
Dimensions	581.5x25.9x37.3mm
Energy efficiency class (EEC)	A++

### Performance data

Rated life L70/B50 [h]	30000
Operating Voltage	220-240V
Ambient Temperature [°C]	-20°C to +40°C
Rated efficacy [lm/W]	94
Total system power	8
Nominal lumens [lm]	750
Rated lumens [lm]	750
Rated power [W]	8
Nominal correlated colour temperature (CCT) [K]	3000
Colour rendering index (CRI) [Ra]	80+

# Optical data

Nominal beam angle [°]	170°
------------------------	------



### Electrical data

Nominal lamp power factor 0.9	9
-------------------------------	---


Controllability	Not dimmable electronic (Static)
-----------------	----------------------------------


### Logistic data


Product status	Available
----------------	-----------

Shipment	Stand	
Chinmont	CTONO	1210
A HICH LELII	314111	10111

#### Photometric Data







### Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)