
TUNGSRAM

Innovation is our heritage EST. 1896







T5 Batten ECO
LBTE 16 WW 4ft ECO
93044482

Product information

The LED T5 Batten designed to be a direct replacement for conventional battens, with energy savings. It offers multiple installation methods to ease your worries and bring the customer a brand new experience of soft lighting. Switch free luminaires. The best choice for smooth linear lighting. We offer this range of 8 luminaires in 4 wattages.



Product data

Mounting type	Surface mount
Brand	GE Lighting
IP Rating	20
Certifications	CE/EAC
Body colour	White
Weight [kg]	0.21
DIALux description	TUNGSRAM - T5 Batten ECO - 1450lm - 16W - 3000K - 80CRI - 93044482[SKU] - Surface mount
IEC protection classes	Class II
Impact resistance (IK)	IK02
Dimensions	1181.5x25.9x37.3mm
Energy efficiency class (EEC)	A+

Performance data

Rated life L70/B50 [h]	30000
Operating Voltage	220-240V
Ambient Temperature [°C]	-20°C to +40°C
Rated efficacy [lm/W]	91
Total system power	16
Nominal lumens [lm]	1450
Rated lumens [lm]	1450
Rated power [W]	16
Nominal correlated colour temperature (CCT) [K]	3000
Colour rendering index (CRI) [Ra]	80+

Optical data

Nominal beam angle [°]	170°
------------------------	------



Electrical data

Nominal lamp power factor	0.	9
---------------------------	----	---


Controllability	Not dimmable electronic (Static)
-----------------	----------------------------------


Logistic data


Product status	Available
----------------	-----------

Shipment	Standard
SHIDHIEHL	Stallualt

Photometric Data







Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)