
TUNGSRAM

Innovation is our heritage EST. 1896







T5 Batten Switch LED Batten G1 TU IP20 8W 2ft 830 S 93107522

Product information

The LED T5 Batten designed to be a direct replacement for conventional battens, with energy savings. It offers multiple installation methods to ease your worries and bring the customer a brand new experience of soft lighting. The luminaire is fitted with an on/off switch for individual operation. The best choice for smooth linear lighting. We offer this range of 8 luminaires in 4 wattages.



T5 Batten Switch LED Batten G1 TU IP20 8W 2ft 830 S 93107522

Product data

Product code	93107522
Description	LED Batten G1 TU IP20 8W 2ft 830 S
DIALux description	TUNGSRAM - T5 Batten Switch - 900lm - 8W - 3000K - 80CRI - 93107522[SKU] - Surface mount
Brand	TUNGSRAM
Product category	Battens
Product family	T5 Switch Batten
Application areas	Office, Retail, Residential
DUN Code	15994100024801
Light source	LED
Sensor	No sensor
Emergency option	No EM
Mounting type	Surface mount
Weight [kg]	0,115
Body color	White
Product dimensions (Length) x (Width) x (Height) [mm]	602 x 24 x 35
Operating temperature min [°C]	-20
Operating temperature max [°C]	40
Rated ambient temperature (tq) [°C]	25
Cooling	Passive
Certifications	CE
General warranty [year]	5

T5 Batten Switch LED Batten G1 TU IP20 8W 2ft 830 S 93107522

Performance data

System power [W]	8
Nominal luminous flux [lm]	900
Rated efficacy [lm/W]	112,5
Rated life L70/B50 [h]	50000
IP front (optical)	20
IP back (electrical)	20
IP Rating	20
Impact resistance (IK)	IK03
Energy efficiency class (EEC)	A+

Photometrical data

Photometric distribution	Wide
Nominal correlated colour temperature (CCT) [K]	3000
Colour rendering index (CRI) [Ra]	>=80
Nominal beam angle [°]	150
UGR value (4H8H)	28.8 / 21.4
Colour consistency in MacAdam steps SDCM	≤6
Photobioligical risk	RG0

Electrical data

IEC protection class	Class II
Operating voltage [V]	220-240V
Rated frequency or frequency range [Hz]	50/60Hz
Lamp input current [mA]	38
Nominal lamp power factor	>=0.85
Controllability	Static




T5 Batten Switch LED Batten G1 TU IP20 8W 2ft 830 S 93107522

Logistic data

Box quantity	1
Shipment	Standard
Product status	Available

Light distribution



Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation Guide (PDF)

Images (HTTP)

DoC document (PDF)

Datasheet (FR) (PDF)

