

Artikel Nr.: 930592

Zubehör, LED-Netzgerät steckerfertig inkl. 6fach Verteiler für Herculis Displayleuchte



IP20 

Elektrische Daten

Betriebsart	stromkonstant	Eingangsspannung	220-240V AC/50-60Hz
Leistung	20,00 W	Leistungsfaktor	
Ausgangsspannung	2-57V DC	Anschlußmöglichkeit	
Ausgangsstrom	350 mA		

Produkteigenschaften

	Schutzklasse II		Überspannungsschutz
SELV	Schutzkleinspannung		Lampenbetriebsgerät 110
	Kurzschlußfest		Möbeleinbau geeignet
	Überlastschutz	ErP	Standby-Stromverbrauch < 0,5 W
	Übertemperaturschutz	LVD	Sicherheit nach EN 61347
	Sicherheitstrafo	EMC	Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
	nicht dimmbar	EMC	Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

Artikel Nr.: 930592

Zubehör, LED-Netzgerät steckerfertig inkl. 6fach Verteiler für Herculis Displayleuchte

Abmessungen und Gewicht**Grenzwerte**

Länge	2475,00 mm	Betriebstemperatur	-20°C - +50°C
Breite	20,00 mm	Gehäusetemperatur	0 °C
Höhe	13,00 mm	max. Menge Sicherungsautomaten	
Durchmesser	0,00 mm	max. Einschaltstrom	
Gewicht	171 g	kapazitive Last	

Article No.: 930592

Accessories, LED power supply unit ready to plug in incl. 6-way distributor for Herculis display light

**IP20 CE****Electrical Characteristics**

Operating mode	constant current	Input voltage	220-240V AC/50-60Hz
Power	20,00 W	Power factor	
Output voltage	2-57V DC	Connection possibility	
Output current	350 mA		

Product features

	Protection class II		Overvoltage protection
SELV	Low voltage protection		Lamp control gear 110
	Short circuit protection		Suitable for furniture installation
	Overload protection	ErP	Standby-power consumption < 0,5 W
	Overheating protection	LVD	Safety according to EN 61347
	Safety transformer	EMC	Interference suppression + immunity according to EN 55015 + EN 61547
	not dimmable	EMC	Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

Article No.: 930592

Accessories, LED power supply unit ready to plug in incl. 6-way distributor for Hercules display light

Dimensions & Weight**Absolute maximum ratings**

Length	2475,00 mm	Operating temperature	-20°C - +50°C
Width	20,00 mm	Case temperature	0 °C
Height	13,00 mm	max. amount of circuit breakers	
Diameter	0,00 mm	max. inrush current	
Product weight	171 g	capacitive load	